






**Enclosures**

Enclosure	Protection Rating	Cable Entry Knockouts	Description	For use with...	Catalog Number	Price	Discount Code
<b>Enclosures for Manual Motor Controller</b>							
	NEMA Type 12 dust-tight	—	Plastic enclosure 200 x 150 x 150 (H x W x D in mm)	PKZ2 PKZ2/ZM	CI19EE-PKZ2-NA		A31
	NEMA Type 1 general purpose	2x 3/4" 1x 1"	Steel enclosure 240 x 170 x 120 (H x W x D in mm)	PKZ2 PKZ2/ZM	CS3-PKZ2		D12

**Through-the-door Mounted Handles for PKZ2**

Accessory	Description	Color	Protection Rating	For use with...	Catalog Number	Price
<b>Door Coupling Handle</b>						
	<ul style="list-style-type: none"> <li>Rotary handle operator</li> <li>Padlockable in OFF and ON positions</li> <li>Includes handle coupling mechanism that accommodates mounting depth of 132 mm</li> </ul> <b>Includes door interlock; not engaged when shipped</b>	Black	NEMA 3R, 4X, 12, 13	PKZ2/ZM PKZ2/S-SP	PKZ2-XH	
		Red/Yellow	NEMA 3R, 4X, 12, 13	PKZ2/ZM PKZ2/S-SP	PKZ2-XRH	
	<ul style="list-style-type: none"> <li>Rotary handle operator</li> <li>Padlockable in OFF and ON positions</li> <li>To be used when PKZ is rotated by 90°</li> <li>Selectable handle positions</li> <li>Includes handle coupling mechanism that accommodates mounting depth of 132 mm</li> </ul> <b>Includes door interlock; not engaged when shipped</b>	Black	NEMA 3R, 4X, 12, 13	PKZ2/ZM PKZ2/S-SP	PKZ2-XH-MCC	
<b>Extension Shaft</b>						
	<ul style="list-style-type: none"> <li>For mounting depths 171 – 300 mm</li> <li>Includes shaft interlock mechanism</li> </ul>	—	—	PKZ2/ZM PKZ2/S-SP	PKZ2-XAH	
<b>Replacement Shaft Coupling</b>						
	Supplied with above handles. Shaft coupling for connection of shaft and handle.	—	—	PKZ2-X(R)H and PKZ0-XAH	PKZ-X(R)H-EAKS	
		—	—	PKZ2-XH-MCC and PKZ0-XAH	PKZ-X(R)H(-MCC)(-M)-EAKS	